



# PIPES - BLACK & GALVANIZED

BS 1387 : 1967

Nominal Bore	inch	Outside Diameter		Thickness		Weight of Plain End				
		Maximum	Minimum	inch	mm	lb/ft	kg/ft	kg/m		
Light	* 1/8	0.396	10.1	0.387	9.7	0.072	1.8	0.243	0.11	0.361
	* 1/4	0.532	13.6	0.518	13.2	0.072	1.8	3.47	0.157	0.517
	* 3/8	0.671	17.1	0.656	16.7	0.072	1.8	0.453	0.205	0.674
	1/2	0.841	21.4	0.825	21	0.08	2	0.64	0.29	0.952
	3/4	1.059	26.9	1.041	26.4	0.092	2.35	0.944	0.428	1.41
	1	1.328	33.8	1.309	33.2	0.104	2.65	1.35	0.612	2.01
	1 1/4	1.67	42.5	1.65	41.9	0.104	2.65	1.73	0.785	2.58
	1 1/2	1.903	48.4	1.882	47.8	0.116	2.9	2.19	0.993	3.25
	2	2.37	60.2	2.347	59.6	0.116	2.9	2.76	1.25	4.11
	2 1/2	2.991	76	2.96	75.2	0.128	3.25	3.9	1.77	5.8
Medium	3	3.491	88.7	3.46	87.9	0.128	3.25	4.58	2.08	6.81
	4	4.481	113.9	4.45	113	0.144	3.65	6.64	3.01	9.89
	* 1/8	0.411	10.4	0.386	9.8	0.08	2	0.273	0.124	0.407
	* 1/4	0.547	13.9	0.522	13.3	0.092	2.35	0.437	0.198	0.65
	* 3/8	0.685	17.4	0.66	16.8	0.092	2.35	0.573	0.26	0.852
	1/2	0.856	21.7	0.831	21.1	0.104	2.65	0.822	0.373	1.22
	3/4	1.072	27.2	1.047	26.6	0.104	2.65	1.06	0.481	1.58
	1	1.346	34.2	1.316	33.4	0.128	3.25	1.64	0.744	2.44
	1 1/4	1.687	42.9	1.657	42.1	0.128	3.25	2.11	0.957	3.14
	1 1/2	1.919	48.8	1.889	48	0.128	3.25	2.43	1.1	3.61
Heavy	2	2.394	60.8	2.354	59.8	0.144	3.65	3.42	1.55	5.1
	2 1/2	3.014	76.6	2.969	75.4	0.144	3.65	4.38	1.99	6.51
	3	3.524	89.5	3.469	88.1	0.16	4.05	5.69	2.58	8.47
	4	4.524	114.9	4.459	113.3	0.176	4.5	8.14	3.69	12.1
	5	5.534	140.6	5.459	138.7	0.192	4.85	10.9	4.94	16.2
	6	6.539	166.1	6.459	164.1	0.192	4.85	12.9	5.85	19.2
	* 1/8	0.411	10.4	0.386	9.8	0.104	2.65	0.331	0.15	0.493
	* 1/4	0.547	13.9	0.522	13.3	0.116	2.9	0.517	0.235	0.769
	* 3/8	0.685	17.4	0.66	16.8	0.116	2.9	0.686	0.311	1.02
	1/2	0.856	21.7	0.831	21.1	0.128	3.25	0.977	0.443	1.45
3/4	1.072	27.2	1.047	26.6	0.128	3.25	1.27	0.576	1.9	
1	1.346	34.2	1.316	33.4	0.16	4.05	2	0.907	2.97	
1 1/4	1.687	42.9	1.657	42.1	0.16	4.05	2.58	1.17	3.84	
1 1/2	1.919	48.8	1.889	48	0.16	4.05	2.98	1.35	4.43	
2	2.394	60.8	2.354	59.8	0.176	4.5	4.14	1.89	6.17	
2 1/2	3.014	76.6	2.969	75.4	0.176	4.5	5.31	2.41	7.9	
3	3.524	89.5	3.469	88.1	0.192	4.85	6.76	3.07	10.1	
4	4.524	114.9	4.459	113.3	0.212	5.4	9.71	4.4	14.4	
5	5.534	140.6	5.459	138.7	0.212	5.4	12	5.44	17.8	
6	6.539	166.1	6.459	164.1	0.212	5.4	14.3	6.49	21.2	

Thickness Tolerance : ± 10%